



Professional DMR Radio
专业数字对讲机

CP395



CP395 Technical Specifications 技术规格

General 一般	CP395U	CP395P
Frequency Range 频率范围	400 - 470 MHz	350 - 400 MHz
Channel 频道数目	512 channels in 16 zones	
Channel Spacing 频道间隔	12.5 kHz(Analog模拟/DMR数字)	
Operating Voltage 工作电压范围	7.4V	
Modulation 调制型式	FM	
Dimension 体积 (H高 x W宽 x D深)	126mm x 59mm x 36mm	
Weight (including battery) 重量 (含电池)	280 g	
Transmitter 发射		
Output Power 射频输出功率	5W - 1 W	3W - 1 W
Frequency Stability 频率稳定	±1.5 PPM (-30 ~ + 60)	
Spurious and Harmonics 杂波辐射	70 dB	
Hum and Noise 调频杂噪声	40 dB	
Audio Distortion 音频失真	3%	
Audio Frequency 音频响应	+3, -3 dB from 6 dB per Octave de-emphasis characteristic from 300 ~ 3000Hz	
Receiver 接收		
Sensitivity 灵敏度 (12 dB SINAD)	0.25uV (-119 dBm)	
Squelch Sensitivity (Threshold) 门限静噪灵敏度	0.22uV (-120 dBm)	
Selectivity 选择性	65 dB	
Intermodulation Rejection 互调抗拒	70 dB	
Spurious and Image Rejection 杂波及镜像抗拒	75 dB	
Audio Output Power 音频输出功率	16 Ω	

Dependable Companion

Designed for tough environments, the CP395 DMR combines the latest technology in a compact aluminum housing. Compatible with Digital / Analog model, making the CP395 suitable for property management and professional industries. (Optional IP67 waterproof available)

Features

- Dual-mode(Analog & DMR) Operation
- 512 Channels in 16 Zones
- Vibration function
- Chinese and English Display
- Remote Radio Stun/Unstun
- Scramble Function Built in LED Flash Light
- Short message (up to 40 characters)
- Recording function (63 parts, 2mins 30 sec/part)
- VOX Voice Activated Transmission
- Emergency Button
- Scan function
- Lone Worker Function
- DC 7.4V 2,600mAh high capacity Battery
- OLED Display
- Emergency / Siren function
- IP54 Rating / Optional IP67 (submersible upto 1 meter for 30 minutes)
- * NXDN Mode

Accessories 配件

CB395 2,600 mAh Li-ion Battery Pack
CS395 Charging Stand & Adaptor (CWC33)

AT33PM / AT33UM Antenna
AT33PL / AT33UL Long Antenna

CPS Telecom Limited

普思电讯有限公司

电话 TEL +852 2185 7888
传真 FAX +852 2187 3111
电邮 sales@cps-telecom.com
WhatsApp / 微信 WeChat 客服热线 +852 5222 1331
www.cps-telecom.com

免责声明 本目录内的内容仅供参考。产品之规格及表现可因改动或实际使用情况而有所差异。对任何一方因直接或间接使用此目录册或其中任何内容而遭受的亏损或损失将不承担任何责任。

Disclaimer The content in this catalog is for reference only. Product specifications and performance may vary due to changes or actual usage. Any party will not be liable for any loss or loss incurred due to the direct or indirect use of this catalog or any of its contents.

您的可靠搭档

CP395DMR在恶劣的环境中保持可靠的性能, 机身严选坚固的铝合金外壳打造, 扎实可靠。其搭载最新数字制式运作系统, 易于使用的界面可确保您的团队可以快速建立联系。(另有IP67防水型号)

特点

- 双模式(模拟/数字)
- 512个工作频道16组
- 震动功能
- 中文及英文显示
- 空中遥毙功能
- 语音整理功能
- 内置LED电筒功能
- 短讯收发(40个字)
- 录音功能(63段, 每段2分30秒)
- VOX 声控发射功能
- 紧急呼叫按键
- 扫描功能
- 独身工作者安全操作模式
- 7.4V 2600mAh锂高分子电池组
- OLED显示屏
- 紧急呼叫
- IP54级别 / 另选型号 IP67防水级别 (一米水深浸泡30分钟)
- * NXDN制式

中国总经销商
快讯电子(惠州)有限公司 Conrad(Huizhou) Ltd
电话 +752 2604 008
传真 +752 2604 022
http://www.conradchina.com